

PLEATED PREFILTER – VilPleat I

PRODUCT DESIGN :

ブリーツブリーツ、綿混紡の合成濾材をエキスパンドダイヤモンドグリッドにラミネートし、酸化を防ぐ特殊仕上げを施しています。

Pleated prefilter, synthetic filter media with cotton blend laminated onto an expanded diamond grid, which features a special finish to prevent oxidation.

PRODUCT DESCRIPTION :

- Compact design
- Specially-finish support grid prevents oxidation
- Chemically-bonded media ensures pleat stability
- Light weight and simple installation and handling
- High performance synthetic fibers

APPLICATIONS :

空調および換気装置の前濾過、または粗い粉塵に対して非常に効果的なシステムでの使用。

Prefiltration for air conditioning and ventilation equipment or using with systems highly effective with coarse dust.

PERFORMANCE :

MODEL	EU Class	Filter Class	Dimension	Actual size	Air Capacity	Pressure Drop
	EN 779	ISO 16890	Inch	mm.	m ³ /h	Pa
VILPLEAT412241	G4	Coarse 70%	12 x 24 x 1	287 x 592 x 22	1700	96
VILPLEAT420241	G4	Coarse 70%	20 x 24 x 1	492 x 592 x 22	2800	96
VILPLEAT424241	G4	Coarse 70%	24 x 24 x 1	592 x 592 x 22	3400	96
VILPLEAT412242	G4	Coarse 70%	12 x 24 x 2	287 x 592 x 44	1700	65
VILPLEAT420242	G4	Coarse 70%	20 x 24 x 2	492 x 592 x 44	2800	65
VILPLEAT424242	G4	Coarse 70%	24 x 24 x 2	592 x 592 x 44	3400	65
VILPLEAT412244	G4	Coarse 70%	12 x 24 x 4	287 x 592 x 95	1700	45
VILPLEAT420244	G4	Coarse 70%	20 x 24 x 4	492 x 592 x 95	2800	45
VILPLEAT424244	G4	Coarse 70%	24 x 24 x 4	592 x 592 x 95	3400	45

SPECIFICATION :

Material	Non woven synthetic cotton blend	Recommended final pressure	200 Pa (Max 250 Pa)
Using temperature	Max. 70°C	Humidity limit	100 % rel. humidity / 90% Cardboard frame
Regenerable	No	Incinerable	Yes, except for metal frame



FILTER CLASS :



FEARURES :



Vilberg

THE ULTIMATE OF AIR FILTERS

100/2 LEABKLONGMON RD, TUB YAO, LADKRABANG, BANGKOK 10520 THAILAND

TEL. (+662)-360-6602, (+6686)-500-3797, (+6687)-054-4416 FAX. (+662)-360-6603

EMAIL : info@filtermatch2002.com , filtermatch2002@hotmail.com WEBSITE : www.filtermatch2002.com



ISO 9001:2015
CERTIFY NO. HK03/0251



ISO 14001:2015
NO. HK03/60492



UL Certified
R26298-20181108