

Synthetic Carbon absorption filter – VSC300

PRODUCT DESIGN :

高品質の活性炭粉末と組み合わせた合成ポリエステル繊維媒体。VSC300は、有害ガス、特にベンゼン、メタノールなどの吸収性能を備えています。

Synthetic polyester fibre media combined with high quality activated carbon powder. VSC300 has absorption performance of harmful gases, particularly benzene, methanol, etc.

PRODUCT DESCRIPTION :

- Synthetic filter coating with activated power coating
- High performance particularly for air or gas cleaning with low concentrations of organic solvent
- High absorption capacity index
- Top cost-benefit ratio

APPLICATIONS :

VSC300はさまざまな目的で使用しています。換気および空調、スプレーブースの汚染防止、産業および公共建設の汚染防止に使用されます。

VSC300 are using for the different purposes. Ventilation and Air condition, Spray-booth pollution controlling, Applied to using for pollution control for industry and public construction.

GENERALS APPEARANCE :

MODEL	UNIT	CARBON FILTER	CARBON FILTER
		VSC300 - 05	VSC300 - 10
APPEARANCE		Media roll	Media roll
MEDIA THICKNESS	mm	5-7	10-12
WEIGHT	g/m ²	250 ± 10%	300 ± 10%
ARRESTANCE DUST SPOT EFFICIENCY	%	80%	88%
FILTER CLASS	EN779 Std.	G3	G4
INITIAL PRESSURE	Pa	45	50
RECOMMENDED FINAL PRESSURE	Pa	250	250
CARBON CONTENT	%	45	58
CARBON TETRACHLORIDE	%	> 28	> 35

SPECIFICATION :

Specific for	VOC up to 200 PPM	Packing	Polyethylene bag
Regenerable	No	Storage condition	Dark, dry, cool and non-ventilation room
Standard roll	2.0 x 20.0 M.	Incinerable	F1 DIN 53438



FILTER CLASS :



FEARURES :



Vilberg
THE ULTIMATE OF AIR FILTERS

100/2 LEABKLONGMON RD, TUB YAO, LADKRABANG, BANGKOK 10520 THAILAND

TEL. (+662)-360-6602, (+6686)-500-3797, (+6687)-054-4416 FAX. (+662)-360-6603

EMAIL : info@filtermatch2002.com , filtermatch2002@hotmail.com WEBSITE : www.filtermatch2002.com



ISO 9001:2015
CERTIFY NO. HK03/0251

ISO 14001:2015
NO. HK03/60492

UL Certified
R26298-20181108